

\*CAMHOUSE

Body	Body Set	수량
EPIC brain	Red EPIC Body	1
Titanium PL Mount	RED MAG 1.8" 128GB or 64Gb SSD Cards(선택)	4
Side SSD Module	RED SSD Station set	1
19mm Bridge Plate / Rods 19mm Long, Short	RED +1 Adapter Module(EVF + LCD)(추가)	1
19mm Ultimate Top Mount / Rods 19mm	HD Onboard Monitor 7" or 5.6"(TVLogic) / Sunshield	1
Easy Top X	HD Monitor 17"(TVLogic) / Sunshield	1
Cheese Handle or Easy Plate XL	Matte Box(MB-14 6.6"x6.6", LMB-5 4"X5.6")	1
RED Quick Plate(V-mount)	Follow Focus(FF-4)	1
REDTouch 5" LCD / Sunshield	Head	1
LCD Cable (2ea)	Tripod(Long, Short, Hihat) Set	1
Magic Arm	IDX Batterys	8
REDmote	Battery Charger	2
Bomb EVF/ UVF Mount (RED, 8")(추가)	ND(IR) 0.3, 0.6, 0.9, 1.2, PL, Clear Filters(6X6, 4X5.6)	1 set
DSMC Side Handle / RED Volt(추가)	Cart set / etc	1
A-BOX(추가)		

\*CAMHOUSE

## EPIC Tech Specs

- **SENSOR** : 14 MEGAPIXEL MYSTERIUM-X™
- **PIXEL ARRAY** : 5120 (h) x 2700 (v)
- **S/N RATIO** : 66db
- **DYNAMIC RANGE** : 13.5 stops, up to 18 stops with HDRx™
- **MAX IMAGE AREA** : 5120 (h) x 2700 (v)
- **LENS COVERAGE** : 27.7mm (h) x 14.6mm (v) x 31.4 mm (d)
- **ACQUISITION FORMATS**
  - 5K RAW (Full Frame, 2:1, 2.4:1 and Anamorphic 2:1)
  - 4.5K RAW (2.4:1)
  - 4K RAW (16:9, HD, 2:1 and Anamorphic 2:1)
  - 3K RAW (16:9, 2:1 and Anamorphic 2:1)
  - 2K RAW (16:9, 2:1 and Anamorphic 2:1)
  - 1080p RGB (16:9)
  - 720p RGB (16:9)
- **PROJECT FRAME RATES** : 23.98, 24, 25, 29.97, 47.96, 48, 50, 59.94 fps, all resolutions
- **DELIVERY FORMATS\***
  - 4K : DPX, TIFF, OpenEXR (RED RAY via optional encoder)
  - 2K : DPX, TIFF, OpenEXR (RED RAY via optional encoder)
  - 1080p RGB or 4:2:2, 720p 4:2:2 : Quicktime, JPEG
  - Avid AAF, MXF. 1080p 4:2:0, 720p 4:2:0 : H.264, .MP4
- **PROGRAM OUTPUT**
  - HD-SDI Clean Feed

-2K RGB, 1080p RGB or 4:2:2, 720p 4:2:2  
-SMPTE Timecode, HANC Metadata, 24-bit 48Khz Audio

•**MONITOR OUTPUT**

-HD-SDI and HDMI with Frame Guides and Look Around  
-2K RGB, 1080p RGB or 4:2:2, 720p RGB or 4:2:2  
-SMPTE Timecode, HANC Metadata, 24-bit 48Khz Audio

•**DIGITAL MEDIA REDMAG (SSD) Module** : (64, 128, 256, 512GB Media)

•**REDCODE™ 12 and 16-bit RAW** : Compression choices of 18:1 to 3:1

1-120 fps 5K, 4.5K  
1-150 fps 4K  
1-200 fps 3K  
1-300 fps 2K

•**AUDIO** : 2 channel, uncompressed, 24 bit, 48kHz.  
-Optional 4 channel, and AES / EBU digital audio.

•**MONITORING OPTIONS** : RED LCD 5" or 9" Touchscreen Display

•**BOMB EVF™ High Definition Viewfinder**

•**REMOTE CONTROL** : Wireless, Ethernet, RS232, GPI Trigger

•**WEIGHT** : 2.26Kg

•**CONSTRUCTION** : Aluminum Alloy

•**TEMPERATURE RANGES: Operating Range**

-0°C to +40°C (32°F to 104°F)  
-Storage Range: -20°C to +50°C (-4°F to 122°F)

•**FROM REDCINE-X**