

*CAMHOUSE

Body	Body Set	수량
RED ONE MX Body	RED ONE MX Body	1
REDFLASH (CF) / RED SSD™ Module(선택)	RED MAG 1.8" 128GB / 64Gb SSD Card RED Flash CF Cards 16Gb (선택) RED Drive 640Gb, 320Gb / RED RAM 128Gb	4 4 1
PL Mount	RED SSD Station set / CF Reader set(선택)	1
19mm Bridge Plate / Rods 19mm Long, Short	HD Onboard Monitor 7" or 5.6"(TVLogic) / Sunshield	1
19mm Top Mount / Rods 19mm	HD Monitor 17"(TVLogic) / Sunshield	1
Top Handle / Extension	Matte Box(MB-14 6.6"x6.6", LMB-5 4"X5.6")	1
RED PRO 5" / 7" On-Board Monitor(선택)	Follow Focus(FF-4)	1
RED PRO EVF / Mount	Head	1
EVF / LCD Cable (2ea)	Tripod(Long, Short, Hihat) Set	1
Magic Arm	IDX Batterys	8
Bebob ML120 IDX Battery Plate	Battery Charger	2
Mni XLR to XLR Audio Cable(추가)	ND(IR) 0.3, 0.6, 0.9, 1.2, PL, Clear Filters(6X6, 4X5.6)	1 set
AC Power Adapter	Cart set / etc	1

*CAMHOUSE

RED ONE MX Specs

- **SENSOR** : 14 MEGAPIXEL MYSTERIUM-X™
- **PIXEL ARRAY** : 5120 (h) x 2700 (v)
- **S/N RATIO** : 66db
- **DYNAMIC RANGE** : 13+ stops
- **MAX IMAGE AREA** : 4480 (h) x 2304 (v)
- **LENS COVERAGE** : 24.2mm (h) x 12.5mm (v) x 27.3 mm (d)
- **DEPTH OF FIELD**
 - Equivalent to S35mm (Motion) lens
 - Equivalent to 16mm (Motion) lens in 2K RAW
- **ACQUISITION FORMATS**
 - 4.5K RAW (2.4:1)
 - 4K RAW (16:9, HD, 2:1, and Anamorphic 2:1)
 - 3K RAW (16:9, 2:1, and Anamorphic 2:1)
 - 2K RAW (16:9, 2:1, and Anamorphic 2:1)
- **PROJECT FRAME RATES**
 - 23.98, 24, 25, 29.97 fps @ 4.5K, 4K
 - plus 50, 59.94fps @ 3K, 2K
- **DELIVERY FORMATS ***
 - 4K : DPX, TIFF, OpenEXR (RED RAY via optional encoder)
 - 2K : DPX, TIFF, OpenEXR (RED RAY via optional encoder)
 - 1080p RGB or 4:2:2, 720p 4:2:2 : Quicktime, JPEG
 - Avid AAF, MXF. 1080p 4:2:0, 720p 4:2:0 : H.264, .MP4

•**MONITOR OUTPUTS**

- HD-SDI and HDMI with Frame Guides and Look Around
- 720p RGB or 4:2:2
- SMPTE Timecode, HANC Metadata, 24-bit 48Khz Audio

•**DIGITAL MEDIA**

- REDFLASH (CF) Module : (16GB Media)
- RED SSD™ (64GB, 128GB, 256GB Capacity)
- RED Drive (128Gb)

•**REDCODE™**

- 12-bit RAW : RC28, 36, 42 Quality Levels
- 1-30 fps 4.5K, 4K
- 1-60 fps 3K
- 1-120 fps 2K

•**AUDIO** : 4 channel, uncompressed, 24 bit, 48KHz.

•**MONITORING OPTIONS**

- RED LCD 5" Flat Panel Display
- RED PRO LCD 7" Flat Panel Display
- BOMB EVF™ High Definition Viewfinder

•**REMOTE CONTROL** : USB-2, GPI Trigger

•**WEIGHT** : 4.53Kg Body Only

•**CONSTRUCTION** : Aluminum Alloy

•**TEMPERATURE RANGES**

- Operating Range: 0°C to +40°C (32°F to 104°F)
- Storage Range: -20°C to +50°C (-4°F to 122°F)

* FROM REDCINE-X